

# LU : Length of Intermediate User Buffer Area

Parameter	Specify . . .	Minimum	Maximum	Default
LU	the size of the intermediate user buffer area.	4000 (see note 1)	65 535 (see note 2)	65 535 (see note 3)

## Notes:

1. The minimum value may be less if a lesser value was specified by the DBA using Adabas Online System.
2. The maximum value must be smaller than the byte count implied by the NAB (number of attached buffers) parameter. For example, the NAB default of 16 allocates more than 64KB. See ADARUN parameter NAB.
3. Due to the length of the record buffer of the utilities that need the nucleus, e.g., ADAULD, the default value is set to 65,535. If the value of LU is less than 65,535 for an Adabas session, a response code will occur when such a utility is running.

The size specified must be large enough to accommodate all Adabas control information (108 bytes), all user buffers (format, record, search, value, ISN) that may be required for any given Adabas command, plus any user information passed from Adabas link routines to nucleus user exits.

If the multifetch/prefetch option or a utility that needs large record/ISN buffers is to be used during the session, the setting of LU must be large enough to contain the buffers needed.

## Example:

Run the Adabas nucleus with an Adabas intermediate user buffer area of 20,000 bytes.

```
ADARUN PROG=ADANUC,LU=20000
```