

Lotus AU/Con-nect: Internet E-mail Nodes

To add an Internet e-mail node, enter a name for the node in the "Mail Node/Type" field at the bottom of the "Administration - External Mail Nodes" screen (this is the name which is to be entered as the addressee when sending mail), and select the Add Mail Node function.

As a result, the "Add Mail Node" screen is displayed. Enter the necessary information for adding a new node. See *Add a Mail Node*. Specify the address level and node type - U for Internet e-mail - and press ENTER. As a result, the "Transport Service Destination Node" window is displayed.

```

3:37 PM          * * * C O N - N E C T 3 * * *          05.Mar.01
Cabinet LS      Administration - Add Mail Node          A06740

      Node Name  IOWA_____  +-----+
      Description _____  !  Transport Service Destination Node  !
      Address Level 8          !-----+
      Node Type  U             !
      A Con-nect   B Telex     F Sn !
      T Teletex   U E-Mail    !
                                     !
                                     !
                                     !
                                     !
      Program Name will be
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---
      Help  Menu  Quit      Displ
Enter data and press ENTER to add

```

The destination node is the local node of the Con-nect transport service (see *Transport Service Node ID*). Specify the destination node and press ENTER.

See *External Mail Nodes* to modify, display, delete or define capabilities for an Internet E-mail node.