

Z-ACCEPT

This chapter covers the following topics:

- Description
 - Parameters
 - Return Codes
 - Subprograms
 - Example
-

Description

Accept or decline an invitation to a meeting.

This subprogram can be used by all attendees. It can also be used for resources.

The Calendar-ISBN must point to a meeting, invitation or cancelation message.

To accept the invitation, mark the parameter Accept with any character. The invitation can be accepted even if it was previously declined, but added to your calendar.

To decline the invitation, leave the parameter Accept blank. The invitation can be declined even if it was previously accepted. When you decline an invitation, it is erased and the meeting is stopped. However, if you mark the parameter Add-to-calendar, the meeting is added to your calendar.

An invitation can only be accepted and added to your calendar if its time range does not conflict with other entries in your calendar. However, if you mark the parameter Add-to-calendar, the invitation is accepted and added to your calendar even if there are conflicting entries.

The following applies for a resource: if you decline an invitation (i.e. leave the parameter Accept blank), the parameter Add-to-calendar is ignored. The meeting is not added to the calendar of the resource.

The following applies for a cancelation message: the parameter Accept is ignored since the cancelation of the meeting is automatically accepted. If you mark the parameter Add-to-calendar, the canceled meeting is added to your calendar.

Date and time when the attendee has displayed the invitation for the first time or changed its state from accepted to declined (or vice versa) is included in the address list. This corresponds to the "Date/Time Read" information that can be displayed in online mode using the ADDRESS command.

Parameters

Parameter	Format	In	Out	Remarks
Return-code	N2		X	
Cabinet	A8	R		The cabinet which contains the cancelation message or the invitation that is to be accepted or declined.
Password	A8	R		The password of the above cabinet.
Calendar-ISBN	P10	R	X	Input: ISBN of the invitation or cancelation message. Output: ISBN of the accepted or declined invitation.
Accept	A1	O		If marked, the invitation is accepted. If not marked, the invitation is declined. For a cancelation message, this parameter is ignored.
Add-to-calendar	A1	O		See the above description. For a resource, this parameter is ignored.

Return Codes

00	Success
02	Invalid cabinet name
03	Password incorrect
04	ISBN was not found
09	ISBN does not point to correct object
18	API context buffer not available
24	Security violation
90	Date/time conflict with existing entry in calendar. Or resource is occupied during this time range.
91	History of meeting cannot be accepted or declined
92	Meeting has already been canceled (cannot be accepted or declined)
93	Resource does not exist

Subprograms

Z-0106A

Z-0106AN

Z-0420

Z-0420A

Z-100

Z-110

Z-120

Z-122

Z-123

Z-124

Z-165

Z-175

Z-180

Z-185

Z-190

Z-194

Z-197

Z-216

Z-222

Z-223

Z-400

Z-401

Z-711

Z-711A

Z-726

Z-728

Z-729

Z-731

Z-736

Z-741

Z-744

Z-745

Z-751

Z-120&0

Example

```
DEFINE DATA
LOCAL
1 RETURN-CODE          (N2)
1 CABINET              (A8)
1 PASSWORD             (A8)
1 CALENDAR-ISN        (P10)
1 ACCEPT              (A1)
1 ADD-TO-CALENDAR     (A1)
END-DEFINE
*
MOVE 'Cabinet' TO CABINET
MOVE 'Password' TO PASSWORD
MOVE 59870 TO CALENDAR-ISN
MOVE 'X' TO ACCEPT
MOVE 'X' TO ADD-TO-CALENDAR
*
CALLNAT 'Z-ACCEPT'
RETURN-CODE
CABINET
PASSWORD
CALENDAR-ISN
ACCEPT
ADD-TO-CALENDAR
*
WRITE
'=' CABINET /
'=' PASSWORD /
'=' CALENDAR-ISN /
'=' ACCEPT /
'=' ADD-TO-CALENDAR //
*
IF RETURN-CODE NE 0
WRITE / 'Return code: ' RETURN-CODE
ELSE
WRITE / 'Return status OK'
END-IF
*
*
```