

Z-ADD11C

This chapter covers the following topics:

- Description
 - Parameters
 - Return Codes
 - Subprograms
-

Description

Add a Con-nect document using data from a text array (A251/1:20).

You can add either a Txt or a Cnf document. The document is always filed in folder Work.

The parameter Text-array must be redefined as:

Byte Number	Description
1	Number of line feeds (1 to 9)
2 to 251	Text

Blank text lines (i.e. line feeds) must be defined separately; for example, when you specify the value 9, this must not be followed by any text. Text lines must always be preceded by the value 1 (when you do not enter a value, 1 is automatically used). For example:

```
MOVE '1This line contains text'    TO TEXT-ARRAY (1)
MOVE '2'                          TO TEXT-ARRAY (2) /* inserts 2 blank lines
MOVE '1This is another text line'  TO TEXT-ARRAY (3)
```

Blank lines after the document text can be suppressed by specifying the number of text lines that are to be stored in the Number parameter. If the Number parameter is not specified, 20 is assumed.

This subprogram can be called iteratively to add a document of any length. During successive calls you must take care that the Work-parameter is not disturbed by the calling routine.

The parameter Text-array is not reset after a call. Thus, when using this subprogram iteratively, you must reset the parameter Text-array before filling it again.

Parameters

Parameter	Format	In	Out	Remarks
Return-code	N2	O	X	Input -1: no ET.
Cabinet	A8	R		The cabinet in which the document is to be added.
Password	A8	R		The password of the above cabinet.
Document-name	A32	R		The name of the document to be added. Need not be specified, if the first line of the Description is specified.
Description	A60/1:4	O		A brief description for the document. If you do not specify a Document-name, you must specify a Description.
Keywords	A15/1:6	O		Keywords are helpful when you search for an object. You can specify up to 6 keywords. A keyword must not contain an asterisk (*).
Document-format	A1	R		0=Txt or 1=Cnf.
Text-array	A251/1:20	R		The text for the document.
Number	N2	O		The number of lines that are stored with each call. When you do not specify a value, or when you specify a value greater than 20, the default value 20 is used.
ISN	P8		X	The ISN of the new document.
Work-parameter	A21			For internal use. See <i>The Work Parameter</i> .

Return Codes

00	Success
02	Invalid cabinet name
03	Password incorrect
51	Invalid name
52	Document with specified name already exists
54	At least one keyword was invalid
58	No directory record has been created
79	Invalid document format

Subprograms

Z-120

Z-122

Z-123

Z-135

Z-162

Z-190

Z-1200&0