

Z-ADDATT

This chapter covers the following topics:

- Description
 - Parameters
 - Return Codes
 - Subprograms
 - Example
-

Description

Add attendees and resources to a meeting.

You can add as many as 12 attendees with each call. To add further attendees, you have to re-invoke this subprogram with no changes to the parameter list - except for the specification of further attendees and attendee types.

Z-ADDATT does not validate the mail information for external attendees. Therefore, each external attendee must be fully defined.

Z-ADDATT creates an address list (if it does not already exist) and performs limited security checking - i.e. it validates the send level and the number of attendees. Valid attendees are reset to blank after checking.

If an attendee is not found or is invalid, the appropriate return code is set. In this case, the attendee is not reset to blank and the API ends.

Caution:

If one of the attendees is not found or is invalid (i.e. if the return code is not 0), no attendees are added to the address list.

Z-MCONFM can later be used to send the invitations.

After the invitations have been sent, Z-UNDO can be used to undo attendees and resources.

Parameters

Parameter	Format	In	Out	Remarks
Return-code	N2	O	X	Input -1: no ET.
Cabinet	A8	R		The cabinet of the originator.
Password	A8	R		The password of the above cabinet.
Originator	A20	O		Will be set to *USER if the originator has an own cabinet. Otherwise, the specified name will be used.
Calendar-ISBN	P10	R	X	Input: ISBN of the first record of the meeting to be modified. Output: ISBN of the first record of the meeting that has been modified.
Attendees	A20/1:12	R	X	Input: the names or user IDs of the attendees. Output: valid attendees are reset to blank.
Attendee-type	N2/1:12	O		One of the following: 1=address (nickname), 5=cabinet, 10=distribution list, 29=resource, 33=user ID, 70=last name, 74=external.
Work-parameter	A128			For internal use. See <i>The Work Parameter</i> .

Return Codes

00	Success
02	Invalid cabinet name
03	Password incorrect
04	ISBN was not found
09	ISBN does not point to a meeting
21	Attendee not found
24	Security violation
25	More attendees than allowed
33	Attendee not unique
34	Attendee type not found
90	Adding attendees is only allowed for the last version of the meeting
91	Attendees cannot be added to a canceled meeting

Subprograms

Z-110
 Z-120
 Z-122
 Z-123
 Z-135
 Z-147
 Z-155
 Z-165
 Z-175
 Z-190
 Z-191A
 Z-194
 Z-197A
 Z-200A
 Z-201
 Z-202
 Z-207
 Z-215
 Z-216
 Z-711
 Z-742
 Z-1200&0

Example

```

DEFINE DATA
LOCAL
1 RETURN-CODE          (N2)
1 CABINET              (A8)
1 PASSWORD             (A8)
1 ORIGINATOR           (A20)
1 CALENDAR-ISN        (P10)
1 ATTENDEES           (A20/1:12)
1 ATTENDEE-TYPE       (N2/1:12)
1 WORK-PARAMETER      (A128)
*
END-DEFINE
*
MOVE 'Cabinet'         TO CABINET
MOVE 'Password'       TO PASSWORD
MOVE 'David Brown'    TO ORIGINATOR
MOVE 102504            TO CALENDAR-ISN
MOVE 'ESH'            TO ATTENDEES(1)
MOVE 33               TO ATTENDEE-TYPE(1)
MOVE 'TPI'            TO ATTENDEES(2)
MOVE 33               TO ATTENDEE-TYPE(2)
*
CALLNAT 'Z-ADDATT'
  RETURN-CODE
  CABINET
  PASSWORD
  ORIGINATOR
  CALENDAR-ISN
  
```

```
ATTENDEES      (*)
ATTENDEE-TYPE (*)
WORK-PARAMETER
*
WRITE
  '=' CABINET           /
  '=' PASSWORD          /
  '=' ORIGINATOR        /
  '=' CALENDAR-ISN      /
  '=' ATTENDEES(*)      /
  '=' ATTENDEE-TYPE(*)  /
*
IF RETURN-CODE NE 0
  WRITE / 'Return code' RETURN-CODE
ELSE
  WRITE / 'Return status OK'
END-IF
*
END
```