

# Z-CAN06

This chapter covers the following topics:

- Description
  - Parameters
  - Return Codes
  - Subprograms
  - Example
- 

## Description

Cancel a meeting.

The following applies for a meeting with version 1: if none of the attendees has read the invitation, all invitations are deleted from the Inbaskets of all attendees and the cancelation message is not sent.

The following applies if the version is greater than 1 or if one of the attendees has already read the invitation: all attendees receive the cancelation message in their Inbaskets.

The cancelation message is not sent, if the meeting occurs in the past.

When the parameter Retain-in-calendar has not been specified, the meeting is erased from the originator's calendar.

Successful termination of Z-CAN06 always results in an END TRANSACTION. You are not able to control transaction handling.

## Parameters

Parameter	Format	In	Out	Remarks
Return-code	N2		X	
Cabinet	A8	R		The cabinet in which the meeting is to be canceled.
Password	A8	R		The password of the above cabinet.
Calendar-ISBN	P10	R	X	Input: ISBN of the first record of the meeting to be canceled. Output: ISBN of the first record of the meeting that has been canceled.
Retain-in-calendar	A1	O		If marked, the meeting is not erased from the originator's calendar after it has been canceled.
Cancelation-message	A37/1:10	O		Text for the cancelation message. If left empty, the standard cancelation message is generated.

## Return Codes

00	Success
02	Invalid cabinet name
03	Password incorrect
04	ISN was not found
09	ISN does not point to correct object
18	API context buffer not available
24	Security violation
90	Unable to create transport service item
98	Meeting has already been canceled and retained in calendar
99	Cancel not allowed from Inbasket

## Subprograms

N-IDATCM  
 N-GETMSG  
 Z-MPPDB  
 Z-MPPLF  
 N-NAMMOD  
 S-0216  
 Z-0106A  
 Z-0106AN  
 Z-0420  
 Z-0420A  
 Z-100  
 Z-110  
 Z-120  
 Z-122  
 Z-123  
 Z-124  
 Z-135  
 Z-147  
 Z-160  
 Z-165  
 Z-168  
 Z-175  
 Z-177  
 Z-180  
 Z-185  
 Z-190  
 Z-191  
 Z-194  
 Z-194A  
 Z-197

Z-208  
Z-209  
Z-210  
Z-211  
Z-212  
Z-213  
Z-216  
Z-222  
Z-223  
Z-224  
Z-225  
Z-241  
Z-373  
Z-400  
Z-401  
Z-402  
Z-403  
Z-404  
Z-406  
Z-407  
Z-711  
Z-711A  
Z-728  
Z-729  
Z-734  
Z-735  
Z-736  
Z-737  
Z-738  
Z-739  
Z-740  
Z-742  
Z-743  
Z-747  
Z-120&0  
Z-RCONFM  
Z-UNDO

See also the list of subprograms for Z-UNDO.

## Example

```
DEFINE DATA
LOCAL
1 RETURN-CODE          (N2)
1 CABINET              (A8)
1 PASSWORD             (A8)
1 CALENDAR-ISN        (P10)
1 RETAIN-IN-CALENDAR  (A1)
1 CANCELATION-MESSAGE (A37/1:10)
END-DEFINE
*
MOVE 'Cabinet' TO CABINET
MOVE 'Password' TO PASSWORD
MOVE 102504 TO CALENDAR-ISN
MOVE 'X' TO RETAIN-IN-CALENDAR
MOVE 'First line of cancelation message ' TO CANCELATION-MESSAGE(1)
MOVE 'Second line of cancelation message' TO CANCELATION-MESSAGE(2)
*
CALLNAT 'Z-CAN06'
RETURN-CODE
CABINET
PASSWORD
CALENDAR-ISN
RETAIN-IN-CALENDAR
CANCELATION-MESSAGE(*)
*
WRITE
'=' CABINET /
'=' PASSWORD /
'=' CALENDAR-ISN /
'=' RETAIN-IN-CALENDAR /
'=' CANCELATION-MESSAGE(*)
*
IF RETURN-CODE NE 0
WRITE / 'Return code' RETURN-CODE
ELSE
WRITE / 'Return status OK'
END-IF
*
END
```