

Directory Synchronization - Upload - Batch Mode Only

This chapter covers the following topics:

- Description
 - Procedure
 - Batch Example
-

Description

Program

B20001

Function

Upload all addresses marked for synchronization to the central directory.

Caution:

You must ensure that the correct setting for the LFILE parameter is specified for the central directory, since in batch mode this information will not be overwritten.

Utility Parameters

None

Procedure

All addresses on your Con-nect node that are marked for synchronization are uploaded to the central directory. This includes the addresses you have physically set for upload and those that were automatically set for upload when you added the addresses to your Con-nect node. See *Directory Synchronization* in *Con-nect Administration* for further information.

For each address uploaded to the central directory, the following data is included in the address' record on your Con-nect node:

1. an alias which uniquely identifies the address on the central directory,
2. name of the central directory to which the address was uploaded, and
3. version number of the directory synchronization programs that were used to upload the address to the central directory.

Additionally, the status for each address is changed to "Uploaded".

This data can be displayed with the Upload Address Maintenance function. See *Directory Synchronization* in *Con-nect Administration* for further information.

Batch Example

Upload all addresses on your Con-nect node that are marked for synchronization to the central directory. This would be coded as follows:

```
LOGON SYSCNT2B  
MENU  
B20001  
FIN
```