

HCDEST - Hardcopy Output Destination

This Natural profile parameter is for mainframes only.

It presets the hardcopy output destination for the terminal command %H (without the *destination* operand). HCDEST=xxx is equivalent to the DEST subparameter of the profile parameter PRINT for Print File 0, that is, PRINT=((0) , DEST=xxx).

Possible settings	1 to 8 characters	Valid hardcopy output destination.
	blank	
Default setting	blank	In some environments, a default destination may be supplied by the operating system or TP monitor. If HCAM=STD is assigned for hardcopy, the default hardcopy output destination is the dataset CMHCOPY.
Dynamic specification	YES	
Specification within session	YES	The hardcopy output destination can be overwritten during the session by specifying "%H <i>destination</i> "; see also the terminal command %H.

If you are running Natural under TSO or in batch mode, the dataset must be defined in the JCL or by dynamic allocation.

Under TSO, the hardcopy dataset specified by HCDEST is closed after %H at the next terminal I/O. The default CMHCOPY dataset is closed not at terminal I/O, but at session termination.

The hardcopy output access method can be specified by profile parameter HCAM or by the DEST subparameter of profile parameter PRINT for Printer 0. More specifications for the hardcopy output file can be made using the profile parameter PRINT or the macro NTPRINT for Printer 0.