

KAPRI - Kanji Printing

This Natural profile parameter is used to specify parameters for Kanji printing. It corresponds to the NTKAPRI macro in the parameter module NATPARM.

For further information, please refer to the Kanji print interface documentation (available from Software AG of Far East).

Possible settings	See below.	Refer to the Kanji print interface documentation.
	OFF	If you do not wish to use the parameter list of the NTKAPRI macro, you specify KAPRI=OFF.
Default setting	None	
Dynamic specification	YES	This parameter can only be specified dynamically. In the Natural parameter module NATPARM, the macro NTKAPRI must be used instead.
Specification within session	NO	

The following topics are covered below:

- KAPRI Parameter Syntax
- NTKAPRI Macro Syntax

KAPRI Parameter Syntax

The KAPRI parameter is specified as follows:

```
NTKAPRI= 'parameter1,parameter2,parameter3,...'
```

The parameters specified with the KAPRI parameter will be appended to the list of parameters specified with the NTKAPRI macro. With a subsequent KAPRI parameter, you can then specify a new parameter list.

NTKAPRI Macro Syntax

The NTKAPRI macro is specified in the Natural parameter module NATPARM as follows:

```
NTKAPRI 'parameter1,parameter2,parameter3,...'
```

If multiple NTKAPRI macros are specified, the parameter lists are concatenated to constitute a single list.