

Terminal Command Key Assignments

The following topics are covered:

- Assigning Terminal Commands to Function Keys
 - CLEAR Key - Interrupt Current Operation
 - CTRL+D Keys - Interrupt Current Operation
 - RESET+ENTER Keys - Attention Interrupt
-

Assigning Terminal Commands to Function Keys

For enhanced operating convenience, you can assign a frequently used terminal command to a function key. The following methods exist:

- Within a Program, you can assign terminal commands to function keys by using the **statement SET KEY**.
- In the programming environment, you can use the **system command KEY** to assign a terminal commands to a function key.
- Function-key assignments can also be made by the Natural administrator via the **profile parameter KEY**.

Note:

Assignments made with the system command KEY are totally independent of assignments made with a SET KEY statement in a program.

CLEAR Key - Interrupt Current Operation

Pressing the CLEAR key has the same effect as the terminal command "%%".

You can also use the CLEAR key to interrupt a recording that is being played back in step mode. Further information on recording is provided in the section Recording in the Natural Utilities documentation.

CTRL+D Keys - Interrupt Current Operation

Note:

This function is only available on mainframe terminals.

Pressing the keys CTRL+D has the same effect as the terminal command "%%".

RESET+ENTER Keys - Attention Interrupt

Note:

This function is only available under Com-plete on terminals connected via a local controller.

Pressing RESET and then ENTER terminates the current processing loop. The loop must contain a database access statement.