

Using the XML Toolkit

The following topics are covered:

- Prerequisite
- Invoking the Application
- PF-Key Assignments

Prerequisite

Natural Version 5 for UNIX is required.

Invoking the Application

The XML toolkit is included in the library SYSEXXT.

To use the XML Toolkit

1. In the Natural command line, enter LOGON SYSEXXT.
2. Enter XML2NAT.
The Main Menu is displayed.

```

08:56:54          *** NATURAL XML Toolkit ***          2002-01-23
                  - Main Menu -                      Library SYSEXXTC

                                Code  Function

                                L   Generate from Natural Data Structure
                                D   Generate from Document Type Definition
                                O   Set up Specific Generation Options

                                Function Code .. _

Press PF4 or PF5 to start generation.
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---
      Help      Exit  LDA   DTD      Optio      Canc
  
```

The following functions are available:

- Generate from Natural Data Structure
Uses the Natural Data Area as a data source.
- Generate from Document Type Definition
Uses the Document Type Definition (.dtd) as a data source.
- Set up Specific Generation Options

For details, refer to the corresponding sections.

PF-Key Assignments

The following function keys are used for navigation and processing.

PF1	Help	Context-related help. For more information, refer to the online documentation.
PF3	Exit	On an options map: closes the function and saves the changes. On a generation map: closes the function after a generation is done. On the Main Menu map: closes the application.
PF7	Prev	Previous step (previous map).
PF8	Next	Next step (next map).
PF9	Finis(h)	Closes the function after a generation is done.
PF12	Cancel	Closes the function without saving the changes. Closes the function if no generation has already be done.