

# Defaults for UNIX

This subsection covers the following topics:

- Invoking the Defaults for UNIX Screen
- Field Descriptions: Defaults for UNIX

---

## Invoking the Defaults for UNIX Screen

If you select UNIX from the window, the following screen appears:

```
21.11.01          *** Entire Operations 4.1.1 ***          08:43:27
Owner EXAMPLE          Defaults for Unix
-----
End-of-Job Checking
  Highest Exit Code accepted as ok   ==> 0_____
Escapes: Activation ==> § Submission ==> ^

Note: Modifications become effective at the next monitor startup.

Command => _____
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---
      Help           End           Save                               Menu
```

## Field Descriptions: Defaults for UNIX

<b>Field</b>	<b>Meaning</b>	
<b>End-of-Job Checking</b>		
Highest Exit Code accepted as ok	The value entered here is the maximum exit code which is accepted as OK.	
<b>Escapes:</b>		
Activation	Activation escape character. This escape character is prefix for Natural code lines and symbols to be replaced at activation time.	
	<b>Note:</b>	Existing Dynamic JCL might become invalid after changing this escape character.
Submission	Submission escape character. This escape character is prefix for symbols to be replaced at submission time.	
	<b>Note:</b>	Existing Dynamic JCL might become invalid after changing this escape character.

These settings become effective after the next Monitor startup and are then used as defaults for new job definitions.