

Network Defaults for VSE/ESA

► To define network defaults for VSE/ESA

1. Press PF6 (Spec) from the Network Modification screen and select operating system VSE/ESA.
2. The Network Defaults (VSE) window opens:

```

04.01.02          *** Entire Operations 4.1.1 ***      11:42:53
Owner SN           N +-----+
Selection OR_____ ! !
- +-----+ ! !
! !
! ! Network Modification ! !
! ! +-----+ ! !
! ! ! ! Network Defaults (VSE) ! !
! ! ! ! ! !
! ! Network      ===> A-1          Owner ===> SN ! !
! ! Description   ===> Time Range Test ... ! !
! ! JCL Node     ===> 148          Execution Node ===> 146 ! !
! ! ! ! ! !
! ! Default Values for the Jobs ! !
! ! Esc Activation ===> _ ! !
! ! Esc Submit    ===> _ ! !
! ! ! ! ! !
! ! --PF1-----PF3-----PF5----- ! !
+--! Help       End      Save ! -+
Comm ! ! !
Enter +-----+ ! !
Help Add End +-----+ 12--- NxtSt Menu

```

3. Enter the network defaults for VSE/ESA in the fields provided:

| Field | Description |
|----------------|--|
| Esc Activation | <p>Activation Escape Character = Network default value specific for operating system This escape character is the prefix for Natural code lines and symbols to be replaced at activation time. CAUTION: Existing Dynamic JCL might become invalid after changing this escape character and applying defaults to jobs.</p> |
| Esc Submit | <p>Submission Escape Character = Network default value specific for operating system This escape character is the prefix for Natural code lines and symbols to be replaced at submission time. CAUTION: Existing Dynamic JCL might become invalid after changing this escape character and applying defaults to jobs.</p> |