

Adding Event Definition (BS2000/OSD)

This section covers the following topics:

- Adding an Event Definition
- Field Descriptions

Adding an Event Definition

▶ To add an event to be checked at job termination

1. Press PF2 (Add) in the End-of-Job Checking and Actions screen.
2. A window opens in which you can enter the event definition:

```

18.11.01          *** Entire Operations 4.1.1 ***          12:20:24
Ow +-----+-----+-----+-----+-----+-----+-----+-----+
Ne !                                                    !
-- !                      Add Event Definition              ! ---
C  !                                                    !
_  !          Event Type ==> _ R User Routine              J Job special event !
_  !                                                    !
_  !                      S String                        A Add. Job-ok, Job-not-ok !
_  !                      U User Switch                  !
_  !                      V Job Variable                  !
_  !                                                    !
_  ! User Routine ==> _____ in NATURAL Library ==> _____ !
_  !                                                    !
_  ! String ==> _____ missing ==> _ !
** ! in File ==> _____ ! ***
_  !                      (Optional) Read Password ==> _____ !
_  !                                                    !
-- ! User Switch ==> 0_ of BS2000 User ID ==> _____ ! ---
A  !                                                    ! her
P  ! Occurrence of event means OK or NOT OK ==> ___ ! Rtn
!                                                    !
Co ! Enter-PF1---PF2---PF3-----PF5-----PF12--- !
Ent !          Help Add   End           Save           Menu ! ---
+-----+-----+-----+-----+-----+-----+-----+-----+

```

Field Descriptions

(BS2000/OSD)

Meaning of the input fields:

Field	Description	
Event Type	Type of event to be checked. Possible values:	
	A	Additional definition for job ok or job not ok . See Example of an A-type Event.
	J	Special event during job execution. See Example of a J-type Event.
	R	Job sysout is to be checked by a user routine. See Example of an R-type Event.
	S	Occurrence of a specific string in job sysout. See Example of an S-type Event.
	U	Event depends on a user switch. See Example of a U-type Event.
	V	Event depends on contents of a job variable . If you enter V , press Enter immediately to open a special window for job variable definition. See Example of a V-type Event.
User Routine	(for an R-type event) Name of the user routine which is to run on job termination. See the subsection Editing End-of-Job User Routines.	
in Natural Library	(for an R-type event) Natural library in which the user routine resides. This library should be different from the Entire Operations system library.	
String	(for an S-type event) Specify the actual string in the job sysout for which Entire Operations is to check.	
(String) missing	(for an S-type event) If you enter Y here, the event occurs if the string is not found.	
in File	(for an S-type event) If you leave this field blank , Entire Operations searches for the String in the sysout collection file created by the Entire Operations Monitor. You can enter another file here to be searched instead. If the file name contains the activation escape character, a symbol replacement is performed (from the active symbol table). The updated file name is stored in the active database.	
User Switch	(for a U-type event) A valid BS2000/OSD user switch must be defined. (Range: 0 through 31).	
BS2000/OSD Userid	(for a U-type event) The BS2000/OSD user ID of the user switch.	
Occurrence of event means OK or NOT OK	Specify event check status if the defined event occurs. Possible values:	
	OK	Check ok .
	NO	Check not ok .
	--	No effect on the job result.

When you are finished defining the event, you can proceed in one of the following ways:

- If you defined an R-type event, you can enter **E** in the line command field of the event on the End-of-Job Checking and Actions screen and press Enter to define the user routine using the Entire Operations Editor. (See the subsection Editing End-of-Job User Routines.)
- Press PF2 (Add) to save the definition and clear the window to add another event. You can define any number of events for any one job.
- Press PF5 (Save) to save the event definition(s).
- Press PF3 (End) to close the window and return to the End-of-Job Checking and Actions screen. The new events are listed on this screen.

