

Natural Nucleus Error Messages NAT7701-NAT7750

NAT7720: Command not applicable in remote environment.

Text	Command not applicable in remote environment.
Expl.	The issued command cannot be executed in a remote (server) environment.
Actn.	Use the appropriate Natural Studio command or tool. In case of a file-operation command, use an equivalent 'Object Menu' operation or 'right mouse button' operation to achieve the desired result.

NAT7721: Command not applicable within the application context.

Text	Command not applicable within the application context.
Expl.	The issued command cannot be executed within the context of an application.
Actn.	Use the appropriate command in the library workspace, or use the right mouse button 'Unlink' command, if you wish to unlink an object from the application.

NAT7722: Command not applicable in local environment.

Text	Command not applicable in local environment.
Expl.	The issued command cannot be executed in a local (client) environment.
Actn.	Use the appropriate Natural Studio command or tool. In case of a file-operation command, use an equivalent 'Object Menu' operation or 'right mouse button' operation to achieve the desired result.

NAT7723: Message from server: :1:

Text	Message from server:
Expl.	The server has sent a message to indicate a special situation. E.g., if, when deleting/renaming a library, one or more objects could not be deleted or renamed (primarily caused by locked objects), the server reports this to the client.

NAT7724: Error during session reconnect.

Text	Error during session reconnect.
Expl.	The Natural Development Server cannot reconnect your session for remote development. Possible reasons are: - corrupted session directory of Natural Development Server, - server address space exceeds specified limit of subtasks, - region size (memory below 16 MB) too small, - Natural Studio requests a reconnect with an invalid session identifier.
Actn.	Examine Natural Development Server trace file for additional error information.

NAT7725: Cannot create new session directory entry or subtask.

Text	Cannot create new session directory entry or subtask.
Expl.	The Natural Development Server cannot create a new entry in its session directory or cannot create a new subtask to process remote development. Possible reasons are: - server address space exceeds specified limit of subtasks, - region size (memory below 16 MB) too small.
Actn.	Examine Natural Development Server trace file for additional error information.

NAT7726: Cannot initialize new session.

Text	Cannot initialize new session.
Expl.	The Natural Development Server cannot perform the basic initialization of a new subtask. Possible reason is shortage of memory above 16 MB.
Actn.	Examine Natural Development Server trace file for additional error information.

NAT7727: Session execution failed.

Text	Session execution failed.
Expl.	The Natural Development Server cannot locate the Natural session in its session directory. Possible reasons are: - the session was cancelled using the server monitor, - the session directory is corrupted, - the Natural Studio requests a reconnect with an invalid session identifier.
Actn.	Examine Natural Development Server trace file for additional error information.

NAT7728: I/O execution not allowed.

Text	I/O execution not allowed.
Expl.	The remote Natural session executes an I/O although I/O execution is not permitted. I/O execution is not permitted during session initialization and Natural Security logon processing.
Actn.	Locate the I/O buffer in the Natural Development Server trace file and contact Software AG support.

NAT7729: Nat. Development Server error - reserved for future use.

Text	Nat. Development Server error - reserved for future use.
------	--

NAT7730: Error during I/O execution.

Text	Error during I/O execution.
Expl.	The Natural Studio returns invalid data for the terminal I/O, or there is not enough memory available above 16 MB.
Actn.	Examine the Natural Development Server trace file for additional error information and contact Software AG support.

NAT7731: Protocol element missing.

Text	Protocol element missing.
Expl.	For the processing of Natural Development Server (NDV) request, the NDV requires protocol data; these were not sent by the Natural Studio.
Actn.	Examine the Natural Development Server trace file for additional error information and contact Software AG support.

NAT7732: NDV not installed on Natural system file.

Text	NDV not installed on Natural system file.
Expl.	The Natural Development Server (NDV) cannot locate the NDV transaction-processor modules on the FNAT system file. The Natural Development Server installation is incomplete.
Actn.	Check whether the Natural Development Server INPL has been executed on the specified FNAT system file.

NAT7733: Library undefined, LOGON required.

Text	Library undefined, LOGON required.
Expl.	The logon library of the Natural Development Server session is undefined. This usually happens if the system command LOGOFF is executed, or if a Natural program executes a RETURN statement and no SETUP record is found.
Actn.	Enter a LOGON command to a valid library of your remote environment or click any library within your remote tree view to continue.

