

Natural under CICS Abend Codes and Error Messages

This section contains the abend codes, SCP environment initialization errors, SCP environment recovery errors, SCP processing errors and the Natural CICS interface session errors issued by the Natural CICS teleprocessing interface.

Unlike Natural system messages, the explanatory long texts to these messages and codes are only available in this document, not online.

This section covers the following topics:

- SCP Environment Initialization Errors
- SCP Environment Recovery Errors
- SCP Processing Errors
- Natural CICS Interface Session Errors

The abend codes and corresponding error messages of the Natural CICS interface are listed groups in the following order:

*NI**nn* SCP environment initialization errors

*NR**nn* SCP environment recovery errors

*NS**nn* SCP processing errors

*NT**nn* Natural under CICS session errors

The Natural System Control Program (SCP) is part of the Natural CICS Interface. A dump is taken for all SCP failures.

SCP Environment Initialization Errors

NIAB - INIT, ABEND *xxxx* DURING INITIALIZATION

Expl.	CICS transaction abend <i>xxxx</i> occurred during system environment initialization.
Actn.	Check the abend code and correct the error or print the dump and contact Software AG Support.

NI01 - INIT, NO STORAGE FOR DIRECTORY EXTENSION

Expl.	At system initialization, the EXEC CICS GETMAIN command for the system directory extension has failed due to a CICS storage bottleneck.
Actn.	Increase CICS dynamic storage.

NI03 - INIT, NO VALID THREADS

Expl.	At system initialization, the system is inoperational because all thread groups are of TYPE=SHR, but there are no valid threads. a) The thread group definitions are setup incorrectly. b) In CICS versions prior to CICS/ESA 3.3: The GETMAIN/GETVIS requests for TYPE=SHR threads have failed. c) In CICS/ESA 3.3 and later: The EXEC CICS GETMAIN SHARED requests for TYPE=SHR thread have failed.
Actn.	a) Check the thread group definitions by the NCMTGD macro in the system directory and make sure that enough storage is available in OSCOR/GETVIS or the relevant CICS (E)DSA to satisfy all TYPE=SHR thread GETMAIN requests. b) Increase OSCOR/GETVIS storage. c) Increase the relevant CICS (E)DSA.

NI04 - INIT, NO CICS ROLL FACILITY AVAILABLE

Expl.	At system initialization, the system has TYPE=SHR or TYPE=GETM thread groups, but no CICS roll facilities are available for these and it has been defined that the NCI system is not to use the Natural Roll Server.
Actn.	If VSAM RRDS roll files are to be used: a) Check if the VSAM RRDS roll files are allocated (IDCAMS DEFINE CLUSTER) and formatted correctly (NATSCPRI program). b) Check if the VSAM RRDS roll files are defined correctly in the CICS start-up JCL and in the CICS FCT. c) Check if the VSAM RRDS roll files are supported at all (ROLLFLS parameter in the NCMPRM macro). d) Check if the VSAM RRDS roll file names are consistent with the Natural under CICS definition (PREFIX parameter of the NCMPRM macro). If CICS auxiliary temporary storage is to be used: e) Check if the TS CI-SIZE IS greater/equal 4K and if the DFHTEMP data set is defined in the CICS start-up JCL. If CICS main temporary storage is to be used: f) Make CICS main temporary storage available as roll facility by specifying a non-zero value in the TSRECSZ in the NCMDIR macro.

NI05 - INIT, ABORTED BY INIT EXIT xxxxxxxx

Expl.	At system initialization, the system initialization exit in NCISTART has aborted the initialization process with return code xxxxxxxx.
Actn.	Contact Software AG Support.

NI07 - INIT, SWAP POOL INSTALLATION FAILURE

Expl.	At system initialization, one of the following has occurred: a) In CICS versions prior to CICS/ESA 3.3: The GETMAIN/GETVIS request for the swap pool failed. b) In CICS/ESA 3.3 and later: The EXEC CICS GETMAIN SHARED request for the swap pool failed.
Actn.	a) Increase OSCOR/GETVIS storage. b) Increase the relevant CICS (E)DSA.

NI08 - INIT, ROLL SERVER NOT ACTIVE

Expl.	It has been defined that the NCI environment is to use the Natural Roll Server (ROLLSRV=YES in NCMDIR), but at system initialization time, it is not active.
Actn.	Start the Natural Roll Server.

NI09 - INIT, SIP SERVER NOT ACTIVE

Expl.	It has been defined that the NCI environment is to be able to switch CICS application regions (parameter CICSPLX=YES in NCMDIR). This requires that the Authorized Services Manager's SIP handler be active, but at system initialization time, it is not.
Actn.	Start the Authorized Services Manager's SIP handler.

SCP Environment Recovery Errors

NRAB - RCVR, ABEND *xxxx* DURING DIRECTORY RECOVERY

Expl.	At system recovery, CICS transaction abend <i>xxxx</i> occurred while recovering the system environment.
Actn.	Print dump and contact Software AG Support.

NR01 - UNABLE TO RECOVER SIR BLOCKS CHAIN

Expl.	At session initialization or termination, the session information record (SIR) blocks' forward and/or backward chain is broken and the system cannot recover from this by means of the system control record.
Actn.	Print dump and contact Software AG Support.

NR02 - THREAD STORAGE OVERFLOW

Expl.	At any SCP request with system integrity checking active, the prefix and suffix of a thread are not consistent.
Actn.	Print dump and contact Software AG Support.

NR03 - THREAD GROUPS (INDEX) FAILURE

Expl.	At an SCP request with system integrity checking being active, one of the following has occurred: <ul style="list-style-type: none"> a) The thread groups index vector is not consistent with the number of thread groups; b) the thread groups index does not point to the corresponding thread group; c) the size of a thread group block is not consistent with its type and definition; d) the name of a thread group does not match the common system prefix.
Actn.	Print dump and contact Software AG Support.

NR04 - DIRECTORY EXTENSION FAILURE

Expl.	The system directory extension is not consistent with the system directory or its eye catcher does not match the common system prefix.
Actn.	Print dump and contact Software AG Support.

NR05 - VSAM ROLL FILES (DIRECTORY) FAILURE

Expl.	It has been defined that the NCI system is not to use the Natural Roll Server. At an SCP request with system integrity checking being active, one of the following has occurred: a) The name of a VSAM roll file does not match the common system prefix; b) the VSAM roll facility RCB slot is not consistent with its online directory bitmap.
Actn.	Print dump and contact Software AG Support.

SCP Processing Errors

NSAB - SCP, ABEND *xxxx* DURING SC P PROCESSING

Expl.	An abend <i>xxxx</i> occurred during SCP processing.
Actn.	Print dump and contact Software AG Support.

NS01 - SCP, GETMAIN FOR IOCB FAILED

Expl.	At session initialization, the EXEC CICS GETMAIN command for IOCB storage of a transaction belonging to a TYPE=NONE thread group has failed due to a CICS storage bottleneck.
Actn.	Increase CICS storage or use a thread-bound transaction ID.

NS02 - SCP, SYSTEM INITIALIZATION/RECOVERY FAILURE *xxxx*

Expl.	The Natural system environment is not operational due to a failure in a previous system initialization or recovery. <i>xxxx</i> indicates the initialization (NI <i>mm</i>) and recovery (NR <i>mm</i>) message code respectively.
Actn.	Determine the reason of the failure. Correct the error and load a new copy of the system directory to restart system initialization.

NS03 - SCP, BB INVALID DURING ROLL-IN

Expl.	At session resumption, the IOCB and BB control block pointers are not consistent or the BB pointed to by IOCB is not in the valid storage range for this session.
Actn.	Print dump and contact Software AG Support.

NS04 - SCP, IOCB NOT FOUND DURING ROLL-IN

Expl.	At session resumption, the IOCB and SIR pointers are not consistent or the IOCB pointer to the session's "old thread" is invalid.
Actn.	Print dump and contact Software AG Support.

NS05 - SCP, NO THREAD AVAILABLE

Expl.	At session initialization or resumption, the EXEC CICS GETMAIN command for thread storage of a transaction belonging to a TYPE=GETM thread group has failed (LENGERR condition when not in 31-bit mode, for example) or a TYPE=SHR thread group has no valid threads or the thread of a non-relocatable session has gone.
Actn.	Print dump and contact Software AG Support.

NS06 - SCP, NO CICS ROLL FACILITY AVAILABLE

Expl.	<p>It has been defined that the NCI system is not to use the Natural Roll Server. At session initialization, no CICS roll facility is available for a new Natural session due to one of the following reasons:</p> <ul style="list-style-type: none"> a) All VSAM RRDS roll files are full or not available and temporary storage is full or not available; b) CICS temporary storage auxiliary is full or not available; c) CICS main temporary storage is not allowed.
Actn.	<ul style="list-style-type: none"> a) Increase the size of the current VSAM RRDS roll file(s) or allocate additional VSAM RRDS roll file(s); b) make CICS auxiliary temporary storage available as Natural roll facility by establishing CISIZE greater/equal 4K; c) specify a non-zero value in the TSRECSZ parameter of the NCMDIR macro to allow main temporary storage.

NS07 - SCP, THREAD GROUP NOT AVAILABLE

Expl.	At session initialization, the TYPE=SHR thread group associated to the current transaction has no valid thread(s).
Actn.	Check the thread group definition by the NCMTGD specification in the system directory generation.

NS08 - SCP, SYSTEM DIRECTORY MISSING/INVALID

Expl.	<p>At an SCP request, one of the following has occurred:</p> <ul style="list-style-type: none"> a) The EXEC CICS LOAD for the Natural system directory has failed (no valid PPT entry / directory name incorrect); b) the loaded directory module is incorrectly linked; c) the loaded directory module is not compatible to NCISTART.
Actn.	<p>Check by means of CEDF which of the explanations applies:</p> <ul style="list-style-type: none"> If a) or b), set up SCP environment correctly; if c), reassemble NCISCPCB with correct macro library.

NS09 - SCP, NO SESSION INFO RECORD AVAILABLE

Expl.	At session initialization, one of the following has occurred: a) the primary SIR block is full and secondary SIR blocks are disallowed; b) the EXEC CICS GETMAIN command for a secondary SIR block has failed due to CICS storage bottleneck; c) at session resumption, SIR and restart data are inconsistent.
Actn.	a) Increase the primary SIR block (first subparameter of the USERS parameter in the NCMDIR macro) or allow secondary SIR blocks (second subparameter of the USERS parameter in the NCMDIR macro); b) increase CICS dynamic storage; c) print dump and contact Software AG Support.

NS10 - SCP, COMPRESSION ERROR DURING ROLL-OUT

Expl.	At session suspension, one of the following has occurred: a) The roll file bitmap in the IOCB is exhausted, i.e., more than 128 records are to be written to the roll facility. b) the size of storage to be rolled out does not fit into the session's VSAM RRDS roll file slot; c) the size of storage to be rolled out is larger than the session's storage currently allocated.
Actn.	If a), redefine the VSAM RRDS or the CICS auxiliary temporary storage size with greater control-interval size; if b) or c), print dump and contact Software AG Support.

NS11 - SCP, BB INVALID DURING ROLL-OUT

Expl.	At session suspension, IOCB and BB pointers are not consistent or the BB pointer in the IOCB is not in the valid storage range of this session.
Actn.	Print dump and contact Software AG Support.

NS12 - xxxxxxxx, ROLL-OUT, FC=ffff, RSP=ccc, RSP2=rrr, eeeeeeee

Expl.	At session suspension, a roll facility I/O request has failed. xxxxxxxx - CICS roll facility name ffff - failing EXEC CICS command (EIB field EIBFN) ccc - EXEC CICS command response code (EIB field EIBRESP) rrr - EXEC CICS command reason code (EIB field EIBRESP2) eeeeeeee - CICS error condition
Actn.	Print dump and contact Software AG Support.

NS13 - xxxxxxxx, ROLL-IN, FC=ffff, RSP=ccc, RSP2=rrr, eeeeeeee

Expl.	At session resumption, a roll facility I/O request has failed. xxxxxxxx - CICS roll facility name ffff - failing EXEC CICS command (EIB field EIBFN) ccc - EXEC CICS command response code (EIB field EIBRESP) rrr - EXEC CICS command reason code (EIB field EIBRESP2) eeeeeeee - CICS error condition
Actn.	Print dump and contact Software AG Support.

NS14 - CNTRL RECORD ACCESS, FC=ffff, RSP=ccc, RSP2=rrr, eeeeeeee

Expl.	At session initialization or termination, access to the SCP system control record has failed. ffff - failing EXEC CICS command (EIB field EIBFN) ccc - EXEC CICS command response code (EIB field EIBRESP) rrr - EXEC CICS command reason code (EIB field EIBRESP2) eeeeeeee - CICS error condition
Actn.	Print dump and contact Software AG Support.

NS15 - SCP, SYNCHRONIZATION, FC=ffff, RSP=ccc, RSP2=rrr, eeeeeeee

Expl.	At session synchronization/serialization, a request as ENQ/DEQ/WAIT EVENT has failed; the following parameters apply: <i>ffff</i> - failing EXEC CICS command (EIB field EIBFN) <i>ccc</i> - EXEC CICS command response code (EIB field EIBRESP) <i>rrr</i> - EXEC CICS command reason code (EIB field EIBRESP2) <i>eeeeeeee</i> - CICS error condition
Actn.	Print dump and contact Software AG Support.

NS16 - SCP, Natural SESSION LOST

Expl.	At session resumption, session data cannot be found, neither in a thread nor in a roll facility.
Actn.	Print dump and contact Software AG Support.

NS17 - SCP, SYSTEM CONTROL RECORD INVALID

Expl.	At session suspension or termination, when trying to release a SIR block, the SCP system control record is inconsistent with the current system.
Actn.	Print dump and contact Software AG Support.

NS18 - SCP, SYSTEM DIRECTORY EXTENSION MISSING/INVALID

Expl.	At an SCP request one of the following has occurred: a) The system directory has no extension; b) the directory and its extension are not consistent.
Actn.	Print dump and contact Software AG Support.

NS21 - SCP, RELOCATION FAILURE *rrrrrrrr* at *xxxxxxx*

Expl.	At session resumption, the relocation process has failed. <i>rrrrrrrr</i> - relocation module return code <i>xxxxxxx</i> - address in error
Actn.	Print dump and contact Software AG Support.

NS22 - SCP, COMPRESSION FAILURE NUS02nn at xxxxxxxx

Expl.	At session suspension, the compression process has failed, see the associated NUS02nn message for detailed information. xxxxxxx - address
Actn.	Print dump and contact Software AG Support.

NS23 - SCP, DE-COMPRESSION FAILURE NUS02nn at xxxxxxxx

Expl.	At session resumption, the decompression process has failed, see the associated NUS02nn message for detailed information. xxxxxxx - address
Actn.	Print dump and contact Software AG Support.

NS30 - ROLL SERVER ALLOC FAILURE, RSP=ccc, RSP2=rrr

Expl.	At session initialization, the request to register a session to the Roll Server has failed. ccc - Roll Server return code rrr - Roll Server reason code
Actn.	Check Roll Server return code and reason code (Reason Codes of the Roll Server Requests). Print dump and contact Software AG Support.

NS31 - ROLL SERVER FREE FAILURE, RSP=ccc, RSP2=rrr

Expl.	At session termination, the request to deregister a session from the Roll Server has failed. ccc - Roll Server return code rrr - Roll Server reason code
Actn.	Check Roll Server return code and reason code (Reason Codes of the Roll Server Requests). Print dump and contact Software AG Support.

NS32 - ROLL SERVER WRITE FAILURE, RSP=ccc, RSP2=rrr

Expl.	At session suspension, the request to pass a session's data to the Roll Server has failed. ccc - Roll Server return code rrr - Roll Server reason code
Actn.	Check Roll Server return and reason code (see Roll Server Messages, Condition Codes and Abend Codes, in the Natural Operations for Mainframes documentation). Print dump and contact Software AG Support.

NS33 - ROLL SERVER READ FAILURE, RSP=ccc, RSP2=rrr

Expl.	At session resumption, the request to retrieve a session's data from the Roll Server has failed. <i>ccc</i> - Roll Server return code <i>rrr</i> - Roll Server reason code
Actn.	Check Roll Server return and reason code (see Roll Server Messages, Condition Codes and Abend Codes, in the Natural Operations for Mainframes documentation). Print dump and contact Software AG Support.

NS34 - ROLL SERVER STATS FAILURE, RSP=ccc, RSP2=rrr

Expl.	A SYSTP utility request for Roll Server Statistics has failed. <i>ccc</i> - Roll Server return code <i>rrr</i> - Roll Server reason code
Actn.	Check Roll Server return and reason code (see Roll Server Messages, Condition Codes and Abend Codes, in the Natural Operations for Mainframes documentation). Print dump and contact Software AG Support.

NS39 - ROLL SERVER NOT ACTIVE

Expl.	The NCI environment is to use the Natural Roll Server (ROLLSRV=YES in NCMDIR), but it is currently not active. No dump is created.
Actn.	Start the Natural Roll Server.

NS40 - SIP SERVER ALLOC FAILURE, RSP=ccc, RSP2=rrr

Expl.	At session initialization, the request to register a session to the Authorized Services Manager's SIP handler has failed. <i>ccc</i> - SIP Server return code <i>rrr</i> - SIP Server reason code
Actn.	Check ASM return code and reason code (see ASM Messages, Condition Codes and Abend Codes, in the Natural Operations for Mainframes documentation). Print dump and contact Software AG Support.

NS41 - SIP SERVER FREE FAILURE, RSP=ccc, RSP2=rrr

Expl.	At session termination, the request to deregister a session from the Authorized Services Manager's SIP handler has failed. ccc - SIP Server return code rrr - SIP Server reason code
Actn.	Check ASM return code and reason code (see ASM Messages, Condition Codes and Abend Codes, in the Natural Operations for Mainframes documentation). Print dump and contact Software AG Support.

NS42 - SIP SERVER READ FAILURE, RSP=ccc, RSP2=rrr

Expl.	At session resumption, the request to retrieve the session's information record (SIR) from the Authorized Services Manager's SIP handler has failed. ccc - SIP Server return code rrr - SIP Server reason code
Actn.	Check ASM return code and reason code (see ASM Messages, Condition Codes and Abend Codes, in the Natural Operations for Mainframes documentation). Print dump and contact Software AG Support.

NS43 - SIP SERVER BROWSE-F FAILURE, RSP=ccc, RSP2=rrr

Expl.	A SYSTP utility request to browse forward through the session information records has failed. ccc - SIP Server return code rrr - SIP Server reason code
Actn.	Check ASM return code and reason code (see ASM Messages, Condition Codes and Abend Codes, in the Natural Operations for Mainframes documentation). Print dump and contact Software AG Support.

NS44 - SIP SERVER BROWSE-B FAILURE, RSP=ccc, RSP2=rrr

Expl.	A SYSTP utility request to browse backward through the session information records has failed. ccc - SIP Server return code rrr - SIP Server reason code
Actn.	Check ASM return code and reason code (see ASM Messages, Condition Codes and Abend Codes, in the Natural Operations for Mainframes documentation). Print dump and contact Software AG Support.

NS45 - SIP SERVER WRITE FAILURE, RSP=ccc, RSP2=rrr

Expl.	At session suspension, the request to pass the session's information record (SIR) to the Authorized Services Manager's SIP handler has failed. ccc - SIP Server return code rrr - SIP Server reason code
Actn.	Check ASM return code and reason code (see ASM Messages, Condition Codes and Abend Codes, in the Natural Operations for Mainframes documentation). Print dump and contact Software AG Support.

NS46 - SIP SERVER QUERY FAILURE, RSP=ccc, RSP2=rrr

Expl.	A SYSTP utility request for SIP Server statistics has failed. ccc - SIP Server return code rrr - SIP Server reason code
Actn.	Check ASM return code and reason code (see ASM Messages, Condition Codes and Abend Codes, in the Natural Operations for Mainframes documentation). Print dump and contact Software AG Support.

NS49 - SIP SERVER NOT ACTIVE

Expl.	The NCI environment has been defined to be able to switch CICS application regions (parameter CICSPLX=YES in NCMDIR). This requires that the Authorized Services Manager's SIP handler is active, but it is currently not. No dump is created.
Actn.	Start the Authorized Services Manager's SIP handler.

NS50 - SWAP MANAGER SWAP POOL INSTALLATION FAILURE (NUSnnnn)**NS51 - SWAP MANAGER SESSION INITIALIZATION FAILURE (NUSnnnn)****NS52 - SWAP MANAGER SESSION ROLL-OUT FAILURE (NUSnnnn)****NS53 - SWAP MANAGER SESSION ROLL-IN FAILURE (NUSnnnn)****NS54 - SWAP MANAGER NORMAL TERMINATION FAILURE (NUSnnnn)****NS55 - SWAP MANAGER ABNORMAL TERMINATION FAILURE (NUSnnnn)**

Expl.	For swap manager failures, NUSnnnn error messages are issued and the transaction is terminated with a dump. The abend code along with the dump depends on the failing swap operation.
Actn.	Print dump and contact Software AG Support.

NS59 - SWAP MANAGER MODULE NATSWPMG NOT INSTALLED

Expl.	The swap manager module NATSWPMG is not linked to the Natural nucleus.
Actn.	Relink the Natural nucleus with module NATSWPMG included.

Natural CICS Interface Session Errors

NTAB - ABORTED DUE TO CRUCIAL SYSTEM FAILURE: *xxxxxxxx*

Expl.	A crucial system failure has occurred; the reason string <i>xxxxxxxx</i> indicates an internal failure mnemonic.
Actn.	Print dump and contact Software AG Support.

NT02 - SESSION WAS CANCELLED BY ADMINISTRATOR *uuuuuuuuu tttt*

Expl.	The user session was cancelled via the system administrator function in SYSTP or via CICS Node Error Program (NEP) processing. <i>uuuuuuuuu</i> - system administrator's user ID (*USER) <i>tttt</i> - system administrator's terminal ID (*INIT-ID)
Actn.	Contact your system administrator.

NT04 - ABORTED BY TERMINAL ID EXIT *xxxxxxxx*

Expl.	At session initialization or resumption, the Natural CICS Interface terminal ID exit NCITIDEX has aborted the session with return code <i>xxxxxxxx</i> .
Actn.	Check the reason for the abortion within your terminal ID exit.

NT05 - EXTERNAL CALLNAT INTERFACE LEVEL FAILURE

Expl.	At terminal I/O, the Natural CICS Interface has detected an inconsistency between the current CICS link level and the Natural external CALLNAT interface level. The session is cancelled.
Actn.	Print dump and contact Software AG Support.

NT06 - SEND ATTEMPTED WITHOUT A TERMINAL

Expl.	Self-explanatory.
Actn.	When *DEVICE=ASYNCR, Natural must not issue screen I/Os (DISPLAY, WRITE, etc.) unless the session parameter SENDER was specified. Restart the session with the SENDER parameter to get the terminal output or check the dump.

NT07 - ERROR AT TASK END: FC=*ffff*, RSP=*ccc*, RSP2=*rrr*, *eeeeeeee*

Expl.	At session suspension or termination, the EXEC CICS RETURN command has failed. <i>ffff</i> - failing EXEC CICS command (EIB field EIBFN) <i>ccc</i> - EXEC CICS command response code (EIB field EIBRESP) <i>rrr</i> - EXEC CICS command reason code (EIB field EIBRESP2) <i>eeeeeeee</i> - CICS error condition
Actn.	Contact Software AG Support.

NT08 - TERMINAL WRITE ERROR FC=*ffff*, RSP=*ccc*, RSP2=*rrr*, *eeeeeeee*

Expl.	An EXEC CICS SEND command has failed. <i>ffff</i> - failing EXEC CICS command (EIB field EIBFN) <i>ccc</i> - EXEC CICS command response code (EIB field EIBRESP) <i>rrr</i> - EXEC CICS command reason code (EIB field EIBRESP2) <i>eeeeeeee</i> - CICS error condition
Actn.	Contact Software AG Support.

NT09 - TERMINAL READ ERROR FC=*ffff*, RSP=*ccc*, RSP2=*rrr*, *eeeeeeee*

Expl.	An EXEC CICS RECEIVE command has failed. <i>ffff</i> - failing EXEC CICS command (EIB field EIBFN) <i>ccc</i> - EXEC CICS command response code (EIB field EIBRESP) <i>rrr</i> - EXEC CICS command reason code (EIB field EIBRESP2) <i>eeeeeeee</i> - CICS error condition
Actn.	Contact Software AG Support.

NT10 - MESSAGE SWITCH ERROR: FC=ffff, RSP=ccc, RSP2=rrr, eeeeeeee

Expl.	An EXEC CICS SEND request of the Natural CICS Interface message switching transaction has failed. <i>ffff</i> - failing EXEC CICS command (EIB field EIBFN) <i>ccc</i> - EXEC CICS command response code (EIB field EIBRESP) <i>rrr</i> - EXEC CICS command reason code (EIB field EIBRESP2) <i>eeeeeeee</i> - CICS error condition
Actn.	Contact Software AG Support.

NT11 - ASYNCH SEND FAILURE: FC=ffff, RSP=ccc, RSP2=rrr, eeeeeeee

Expl.	An asynchronous Natural session has failed to route a message to the facility (terminal/destination) specified via the SENDER/OUTDEST session parameters. <i>ffff</i> - failing EXEC CICS command (EIB field EIBFN) <i>ccc</i> - EXEC CICS command response code (EIB field EIBRESP) <i>rrr</i> - EXEC CICS command reason code (EIB field EIBRESP2) <i>eeeeeeee</i> - CICS error condition
Actn.	Check the failing CICS command and response code.

NT89 - xxxxxxxx, INCOMPATIBLE CICS VERSION: MACLIB=xxxx SYSTEM=yyyy

Expl.	The indicated module has been assembled with macros of a CICS version <i>xxxx</i> , which is different to the one which is currently active (<i>yyyy</i>).
Actn.	Assemble NCISTART with the correct CICS macro library.

NT90 - xxxxxxxx, BACK-END PROGRAM/TRANSACTION MISSING (eeeeeeee)

Expl.	The back-end program or transaction specified via front-end program of session parameter PROGRAM or CALLNAT 'CMPGMSET' does not exist; back-end transactions have a back-end "program" name "STR= <i>xxxx</i> " or "RET= <i>xxxx</i> ". <i>eeeeeeee</i> - CICS error condition.
Actn.	Check the program or name and its CICS PPT and PCT entry respectively.

NT91 - xxxxxxxx, ADABAS LINKAGE ROUTINE MISSING/INVALID (eeeeeeee)

Expl.	<p>a) A CICS LINK/LOAD request for the indicated module has failed.</p> <p><i>eeeeeeee</i> - CICS error condition.</p> <p>b) The requested module is not a valid CICS command level program.</p>
Actn.	<p>a) Check if the ADANAME session parameter specifies the correct Adabas linkage program, if it is defined in the CICS PPT and if it is linked in a library available to CICS.</p> <p>b) Check if the module named by the ADANAME session parameter is the Adabas command level version and if it is linked correctly.</p>

NT92 - xxxxxxxx, Natural NUCLEUS MODULE MISSING/INVALID (eeeeeeee)

Expl.	<p>For xxxxxxxx = NATPARM:</p> <p>a) NATPARM is not linked to the CICS interface for xxxxxxxx = NATSTUB.</p> <p>b) NATSTUB is not linked to the CICS interface, while the Natural nucleus is linked to it.</p> <p>c) NATSTUB is not the entry point of the shared Natural nucleus which is not linked to the CICS interface.</p> <p>Else:</p> <p>d) Unable to load the shared Natural nucleus module xxxxxxxx.eeeeeeee - CICS error condition.</p>
Actn.	<p>a) Link the Natural parameter module to the CICS interface.</p> <p>b) Link module NATSTUB to the CICS interface.</p> <p>c) Specify entry point CMSTUB linking the shared Natural or specify the correct module in the NUCNAME session parameter.</p> <p>d) Check if session parameter NUCNAME is consistent with the CICS PPT definition and if the shared Natural nucleus has been linked correctly.</p> <p>For OS/390 only: If the shared Natural nucleus is to be loaded into the LPA/ELPA, check the CICS ALT definition and check if LPA=YES has been specified in the CICS SIT or startup parameters.</p>

NT93 - xxxxxxxx, Natural DRIVER MODULE MISSING/INVALID

Expl.	The indicated module is not linked or invalid or does not have the same SM level as the CICS interface.
Actn.	Link the correct module to the CICS interface.

NT94 - xxxxxxxx, MANDATORY MODULE NOT ACCESSIBLE

Expl.	The indicated module is not accessible by the Natural CICS Interface, because a) it resides "above the line", whereas NCISTART runs in 24-bit mode (the shared Natural nucleus, for example); b) it cannot be modified.
Actn.	a) Link the Natural CICS Interface and the indicated module with consistent AMODE/RMODE. b) Link the indicated module with NORENT option and define it with EXECKEY=USER in the CICS PPT (CICS 3.3 and above).

NT95 - TRANSACTION xxxx, TWA SIZE TOO SMALL

Expl.	The size of the transaction work area for Natural is too small. It must be at least 128 bytes.
Actn.	Correct the TWASIZE parameter in the CICS PCT entry for transaction xxxx.

NT96 - Natural TRANSACTION xxxx MISSING/INVALID

Expl.	The Natural pseudo-conversational restart transaction ID specified in a front-end parameter list does not exist.
Actn.	Check the transaction code and its CICS PCT entry.

NT97 - Natural HAS BEEN RESET, PLEASE RESTART

Expl.	A new copy of the Natural under CICS system directory module has been loaded. Existing sessions cannot survive.
Actn.	The session is terminated.

NT98 - SESSION TERMINATED, xxxx ABEND OCCURRED

Expl.	An abend xxxx has occurred and Natural is unable to continue.
Actn.	The session will be terminated with a dump.

NT99 - SESSION TERMINATED, UNRECOVERABLE ABEND xxxx/yyyy

Expl.	A second abend xxxx has occurred while processing abend yyyy.
Actn.	The session is terminated with a dump. Specify parameter DU=ON and reproduce the problem to get a dump for the first abend.