

Optimizer Options

When Natural Optimizer has been activated, you can indicate further specifications with various options explained in this section.

The Optimizer options consist of a string surrounded by brackets or single quotation marks (except in the Natural OPTIONS statement), with options separated by commas. Some options have values, while the very existence of some options in the option string is sufficient to modify the environment.

Below is information on:

- List of Options
- PGEN Option
- Influence of other Natural Parameters

List of Options

The following table lists and describes Optimizer options. Default values are underlined (this is the value that will be assumed if the option is not present). Optional clauses are surrounded by square brackets [], choices are surrounded by curly braces { } and each choice is separated by vertical lines "|". Only one of these choices may be specified; ON is equivalent to Y (Yes), OFF to N (No). Options specified without the optional clause ON or OFF (if applicable), or their equivalent values, are interpreted as set to ON. For example, OVFLW is identical with OVFLW=ON.

Option	Explanation
ABEND	Forces the Natural Optimizer Compiler to generate code which causes Natural to be abnormally terminated immediately when the ABEND option is encountered by the Natural Optimizer Compiler during compilation. The option must appear by itself or it will be ignored. Other parameters are not changed or reset by this option. This option may be useful for debugging purposes.
CACHE[={ <u>ON</u> OFF Y N}]	Applies to NOC Version 3.1.5 only. Switches variable caching on or off. See also Variable Caching in the section Performance Considerations.
CPU= <u>/370</u>	Specifies the target architecture. The /370 option is valid for IBM and Siemens.
DIGTCHCK[={ON <u>OFF</u> Y N}]	Applies to NOC Version 3.1.5 only. Specifies whether the digits of zoned and packed fields are to be checked when moving to another variable of the same type and precision. For example, if DIGTCHCK is ON and a zoned decimal variable contains an invalid digit, such as X'FA', moving to another zoned variable with the same precision will generate a S0C7 (or NAT0954) error. If DIGTCHCK is OFF, no error is generated but the generated code is much faster.
ERRDUMP[={ON <u>OFF</u> Y N}]	Specifies whether MCG should abend if an error condition is detected during the compile phase. This is useful for debugging the Natural Optimizer Compiler itself.
INDEX[={ON <u>OFF</u> Y N}]	Specifies whether array indexes will be checked for out-of-bound values in the optimized code. See also the Warning below.
INDX[={ON <u>OFF</u> Y N}]	Specifies whether array indexes will be checked for out-of-bound values in the optimized code. Additionally, RANGE will be set on. Therefore, this option is equivalent to INDEX=ON,RANGE=ON. See also the Warning below.

Option	Explanation
IO[={ON OFF Y N}]	Reserved for future use.
LOOPS[={ON OFF Y N}]	Specifies whether loops should be compiled without a loop table entry. To be used only if there are no places in the program containing ESCAPE where the target cannot be determined at compile time. Should be used with caution.
MIX[={ON OFF Y N}]	Provided for compatibility reasons only. No effect.
NODBG[={ON OFF Y N}]	<p>If NODBG=OFF/N (default), the Natural Debugger can be used to debug optimized code (then, additional code is generated to check whether TEST mode has been set on).</p> <p>If NODBG=ON/Y, it is not possible to use the Natural Debugger to debug optimized programs. The program will also run faster and consume less CPU time.</p> <p>See also NODBG in the section Performance Considerations (applies to NOC Version 3.1.5 only).</p> <p>Attention NOC Version 2.3: If OVFLW, INDX, INDEX or RANGE is specified, NODBG=OFF/N is assumed, any other value is ignored.</p>
NOSGNTR[={ON OFF Y N}]	<p>Applies to packed numbers only.</p> <p>Applies to NOC Version 3.1.5 only: If NOSGNTR=OFF (default), signs of positive packed numbers which are the result of an arithmetic operation or the target of an assignment are set according to the PSIGNF parameter. If NOSGNTR=ON, the signs resulting from execution of the generated machine instruction are left unchanged. See also the section Influence of other Natural Parameters.</p> <p>NOC Version 2.3: NOSGNTR=OFF (default), signs of positive packed and unpacked numbers which are the result of an arithmetic operation or the target of an assignment are set to X'F'. If NOSGNTR=ON, the signs resulting from execution of the generated machine instruction are left unchanged, i.e., the signs of positive numbers will be X'C'.</p>
ON	Switches on optimizing. If no additional option is specified, the default value defined for each option is in effect. As indicated in the Warning below, this may cause unintended results, in particular regarding the options INDEX, INDX, OVFLW, and RANGE.
OFF	Switches off optimizing.
OPTLEV={2 3}	<p>Specifies optimization level - roughly equivalent to the number of passes through the program.</p> <p>OPTLEV=3 is useful when PGEN is specified, since some branch targets cannot be determined during the first pass and PGEN output is made during the last pass. Thus, some values may be shown improperly.</p>
OVFLW[={ON OFF Y N}]	<p>Specifies whether checks for overflow in arithmetic operations or assignments will be included in the optimized code.</p> <p>See also the Warning below.</p>
PGEN[={ON OFF Y N}]	Specifies whether a disassembly of the optimized code should be output. This option also enables all other tracing options. See also PGEN Option below.

Option	Explanation
RANGE[={ON OFF Y N}]	Specifies whether range checks will be performed in operations with arrays. This ensures that array ranges will have an equal number of elements in corresponding dimensions of all operands. See also the Warning below.
SIGNCHCK[={ON OFF Y N}]	Applies to NOC Version 3.1.5 only. Specifies whether the result of a multiplication with a packed or zoned multiplier should be checked for a negative zero. If zero is multiplied by a negative number, the MP machine instruction generates a negative zero result. If SIGNCHCK is on, this negative zero is converted to a positive zero. The check for a negative zero is done for every multiplication with a packed or zoned multiplier.
ZD[={ON OFF Y N}]	Specifies whether divisors should be checked for zero. If this option is specified, then code is inserted, so that the program behaves according to the ZD profile parameter of Natural, that is, Natural error NAT1302 is issued or the result is zero. If this option is not specified, Natural error NAT0954 occurs if the divisor is zero. See also ZD - Zero-Division Check in the section Profile Parameters in the Natural Parameter Reference documentation.



Warning for INDEX, INDX, OVFLW, and RANGE:

Apply values OFF and N with care. Suppressing overflow checking or array index checking may allow that incorrect programs lead to unpredictable results, storage corruptions, or abnormal terminations.

PGEN Option

The PGEN option causes the Natural Optimizer Compiler to output the generated code and internal Natural structures. Thus, code and structures can be examined, for example, for bug fixing, performance review and support issues.

An understanding of IBM's /370 assembler is required to interpret the results produced by the PGEN option.

We recommend that you use this option with the assistance of your local Software AG representative.

Below is information on:

- Setting PGEN
- Sub-Options of the PGEN Option
- Output of the PGEN Option
- Working with the PGEN Output

Setting PGEN

To use the PGEN facility, set the PGEN option when activating on the Optimizer Compiler.

Since the buffer is kept in memory, it is possible that the user thread will not be big enough to hold the trace information. In this case, try setting PGEN on only for the portion of the program which is to be traced, for example:

OPTIONS MCG=(PGEN=ON , TRGPT=ON) or OPTIONS MCG=+PGEN , TRGPT	Turns tracing on, including tracing of the GPT entries
OPTIONS MCG=(PGEN=OFF) or OPTIONS MCG=-PGEN	Turns tracing off

Various options affect the content of the output. The basic PGEN option causes a formatted listing of Natural source lines and a disassembly of the corresponding code to be generated and kept in memory for extraction by the NOCSHOW utility as described below, under Output of the PGEN Option.

The TRSTMT, TRGPT, TRMPT and TRVDT options cause hex dumps of internal data structures associated with each line to be output.

Applies to NOC Version 3.1.5 only:

The TRBASES and TRCACHE options cause information on base registers and cache variables to be printed out.

Sub-Options of the PGEN Option

The following table describes the options when PGEN=ON. For an explanation of the syntax used see the introduction to List of Options above.

Option	Explanation
LPP={5 ..55 ..255}	Lines-per-page for the trace output, only used when TREXT=ON.
NOSRCE[={ON OFF Y N}]	If NOSRCE=OFF, the Natural source statement is included in the output.
TRACELEV={0 ..255}	Specifies the trace level. Each bit in this one byte value specifies a buffer type to trace; these bits can be set on by using the TRxxx options as well.
TRBASES[={ON OFF Y N}]	Applies to NOC Version 3.1.5 only. Specifies whether base register allocations are traced.
TRCACHE[={ON OFF Y N}]	Applies to NOC Version 3.1.5 only. Specifies whether CACHE entries are traced.
TREXT[={ON OFF Y N}]	If TREXT=ON, trace is directed to the user exit NOCPRINT as described below.
TRGPT[={ON OFF Y N}]	Specifies whether GPT entries are traced.
TRMPT[={ON OFF Y N}]	Specifies whether MPT entries are traced.
TRSTMT[={ON OFF Y N}]	Specifies whether STMT entries are traced.
TRVDT[={ON OFF Y N}]	Specifies whether VDT entries are traced.

See also the examples below.

Output of the PGEN Option

There are two places to where the Natural Optimizer Compiler can direct the output of PGEN:

- Internal Buffer
- User Exit NOCPRINT

Internal Buffer

The contents of this buffer is overwritten each time a CHECK, CAT, STOW or RUN command is executed. A system utility NOCSHOW is provided whereby the contents of this buffer can be viewed, searched or printed.

To invoke the NOCSHOW utility

- Enter the direct command NOCSHOW after a CHECK, STOW, CAT or RUN where the Natural Optimizer Compiler has been active.

The following PF keys are available on the screen:

Key	Function
PF2	Position to top of output
PF4	Position one line backward
PF5	Position one line forward
PF6	Print to Natural printer support No.1
PF7	Position one page backward
PF8	Position one page forward
PF10	Scan for text string
PF11	Repeat scan

User Exit NOCPRINT

If TREXT=ON is specified, the Natural Optimizer Compiler passes every output line to the user exit NOCPRINT instead of adding it to the trace buffer.

NOCPRINT is invoked following normal OS register conventions. Register 1 points to a full word containing the address of the 81 byte print line with ANSI carriage control characters in position 1. Register 13 points to an area of 18*4 bytes which may be used as a save area. Register 14 contains the return address and Register 15 contains the entry address of NOCPRINT.

The user exit NOCPRINT can be written in any language which supports the register conventions described above. It must be linked to the Natural nucleus together with the Natural Optimizer Compiler nucleus.

Working with the PGEN Output

This section provides hints and explanations on how to interpret the output created with the PGEN option.

- At the top of the PGEN output are some disassembled lines which do not appear to belong to any source line. These are the instructions which make up the prologue, which is executed whenever control passes from non-optimized to optimized code. Permanent base registers are loaded and control is passed to the correct point in the prologue.
See Example Section A below.
- Sometimes a lot of source lines are printed without any code. This is because the Natural compiler puts a single line number in the object of statements which may span more than one line.
See Example Section B below.
- If the NODBG=OFF (default) has been specified, a sequence of instructions is generated at the start of each Natural statement:

```
BALR R9,R11
DC X'....'
```

This sequence sets the line number (in case of error) and checks whether the TEST mode is switched ON. Without this sequence, debugging of NOC-compiled statements by the Natural Debugger is not possible. See Example Section C below.

- Sometimes there is a line break between disassembled lines. This break indicates an internal statement separation. It happens because often a single Natural statement will generate multiple internal (pseudo-code) statements.

Example Section A:

```
000000 5880 D354          L      R8,RTADR+4
000004 5870 D370          L      R7,RTADR+32
000008 4810 6006          LH     R1,6(,R6)
00000C 1F60              SLR   R6,R0
00000E 47F1 A000          BC    15,0(R1,R10)
```

Example Section B:

```
0010 OPTIONS MCG=(PGEN=ON,TRGPT=ON)
0020 DEFINE DATA LOCAL
0030 1 I(I4)
0040 1 P(P7.2)
0050 1 T(P7.2)
0060 END-DEFINE
0070 *

0080 SETTIME
0090 *

000012 45E0 B040          BAL   R14,RETH
000016 0036              DC    X'0036'

0100 FOR I=1 TO 100000
```

Example Section C:

```

000018 059B          BALR  R9,R11
00001A 003E          DC    X'003E'
00001C D203 7000 833B MVC    I,#VAR033B

000022 059B          BALR  R9,R11
000024 004C          DC    X'004C'
000026 47F0 A040     BC    15,64(,R10)

00002A 059B          BALR  R9,R11
00002C 005A          DC    X'005A'
00002E BFFF 8343     ICM   R15,15,#VAR0343
000032 BF0F 7000     ICM   R0,15,I
000036 1A0F          AR    R0,R15
000038 BE0F 7000     STCM  R0,15,I

00003C 059B          BALR  R9,R11
00003E 006C          DC    X'006C'
000040 BFFF 833F     ICM   R15,15,#VAR033F
000044 BF0F 7000     ICM   R0,15,I
000048 190F          CR    R0,R15
00004A 4720 A066     BC    2,102(,R10)

0110  ADD 1.00 TO P

00004E 059B          BALR  R9,R11
000050 0082          DC    X'0082'
000052 FA41 7004 8347 AP    P,#VAR0347
000058 DC00 7008 B488 TR    P+4(1),PSGNTR

0120 END-FOR
0130 *

00005E 059B          BALR  R9,R11
000060 0094          DC    X'0094'
000062 47F0 A02A     BC    15,42(,R10)

0140 T:=*TIMD(0080)

000066 059B          BALR  R9,R11
000068 009C          DC    X'009C'
00006A 45E0 B0D8     BAL   R14,SYSFUNC
00006E 0330 B881     DC    X'0330B881'

000072 F246 7009 8330 PACK  T,#VAR0330
000078 F040 7009 0002 SRP   T,2,0
00007E DC00 700D B488 TR    T+4(1),PSGNTR

0150 T:=T / 10
0160 *

000084 059B          BALR  R9,R11
000086 00AE          DC    X'00AE'
000088 F864 D100 7009 ZAP   OP1(7),T
00008E F811 D130 8349 ZAP   WORK2(2),#VAR0349
000094 45E0 B104     BAL   R14,ZDCHECK
000098 F240 7009 B355 PACK  T,ZEROZ
00009E 47F0 E01C     BC    15,28(,R14)
0000A2 FD61 D100 8349 DP    OP1(7),#VAR0349
0000A8 D204 7009 D100 MVC   T,OP1
0000AE DC00 700D B488 TR    T+4(1),PSGNTR

```

```

0170 DISPLAY 'ELAPSED TIME (S)' T

0000B4 45E0 B040          BAL   R14,RETH
0000B8 00C0          DC    X'00C0'

0180 END
    
```

Influence of other Natural Parameters

The global parameter ZD influences the behavior of the NOC compiler. See the description of the ZD option as described under List of Options above.

Applies to NOC Version 3.1.5 only:

The COMPOPT parameter PSIGNF (see also the system command COMPOPT in the Natural Command Reference documentation) influences the behavior by forcing the signs of positive packed decimal numbers to **F** if ON, and to **C** if OFF. The parameter is applied if NOSGNTR=OFF is specified.

See the chart below for packed data (Type P):

NOSGNTR=OFF	and	PSIGNF=ON	All signs are normalized to F (default).
NOSGNTR=OFF	and	PSIGNF=OFF	All signs are normalized to C.
NOSGNTR=ON			All signs are left as they were generated by the last operation.

For numeric data (Type N) the signs are always normalized to F, regardless of the settings of NOSGNTR and PSIGNF.